

Tononforty Zenit 102-A STD

Specifications

Производитель	Tononforty
Тип	Zenit 102-A STD
Тип продукта	Air Cooled Chiller
кВт	48,7
Мощность, тонн	13,7
Хладагент	Freon
Тип хладагента	R410A
Pump	✓
гидромодулем	✓
Масса	553
Sizes	2000x1150x1000 mm (LxWxH)
Compressor(s) type & model	Panasonic C-SCP315H38B (2x)
Display	Emerson
Number of fans	1
Примечания	y.o.b. 2016
Stock	1



Description

Used Tononforty Zenit 102-A STD

Used Tononforty Zenit 102-A STD air cooled water chiller / heatpump on R410A Complete with 2x Panasonic C-SCP315H38B scroll compressors. The chiller uses 1 fan. Power: 50 Hz - 3 Ph. Waterpump Lowara CEA210/2V/D. Y.o.b. 2016.

*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform a industrial cleaning. if requested we can arrange your shipment.



TONONFORTY		CE
MODELLO - MODEL	N° DI MATRICOLA - SERIAL N°	ANNO - YEAR
ZENIT 102 - A STD	2016010000025	2016
POTENZIALITÀ FRIGORIFERA KALTELEISTUNG POISSANCE FRIGORIFIQUE	kW	48,7
POTENZIALITÀ TERMICA WÄRMELISTUNG POISSANCE THERMIQUE	kW	54,6
REFRIGERANTE KÄLTMITTEL FLUIDE FRIGORIFÈRE	type - kg	R410A/16KG
TEMPERATURE MAX REFRIG TEMP MAX REFRIGERANT TEMP MAX REFRIGERANT	°C - bar	115 / 42
DEBITO PRINCIPALE KÄLTLEISTUNG CAPACITÉ PRINCIPALES	m³/h	1
TENSIONE DI ALIMENTAZIONE POTENZA TENSION D'ALIMENTATION PUISSANCE	V	400V/3P/50Hz
TENSIONE DI ALIMENTAZIONE AUSILIARI TENSION D'ALIMENTATION AUXILIAIRES	V	230/24
POTENZA MAX ASSORBITA MAX POWER CONSUMED MAX POWER CONSUMED	kW	23,90
CORRENTE MAX ASSORBITA MAX CURRENT MAX CURRENT	A	40,60
CORRENTE MAX DI SPUNTO MAX STARTING CURRENT MAX STARTING CURRENT	A	131,10
INTENSITÀ DI DEMARRAGE PROTEZIONE DEMARAGE	IP	X4
MAX PRESSURE CIRCUIT MAX PRESSURE CIRCUIT	MPa	600



