

Carrier 30 HXC 130

Specifications

Производитель	Carrier
Тип	30 HXC 130
Тип продукта	Water Cooled Chiller
кВт	450,0
Мощность, тонн	128,0
Хладагент	Freon
Тип хладагента	R134A
Масса	2.474
Sizes	3600x1000x2000 mm (LxWxH)
Compressor(s) type & model	1 Carrier 06NW2250S7NC & 1 Carrier 06NW2209S7NC
Display	Carrier Pro-Dialog Plus
Примечания	Y.o.b. 2008
Stock	1



Description

Used Carrier 30 HXC 130

Used Carrier 30 HXC 130 water cooled chiller on R134A. Complete with 1 Carrier 06NW2250S7NC & 1 Carrier 06NW2209S7NC screw compressor, shell and tube as evaporator with a water volume of 65 liter, Carrier 09RX2100FA-216-PEE-- shell and tube as condenser with a water volume of 78 liter and a Carrier Pro-Dialog Plus. *All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.



1 - (FR) NUMERO DE SERIE
(EN) SERIAL NUMBER
(DE) SERIENNUMMER

12Y819624

2 - MODELE - MODEL
MODELLNUMMER

30HXC130-A0430-PEE - -

3 - VARIANTE VARIANT
VARIANTE

30HXC

4 - ANNEE DE FABRICATION ET DATE D'ESSAI
YEAR OF MANUFACTURING AND TEST DATE
HERSTELLUNGSJAHR UND DATUM

25/11/2008

5 - FLUIDE - FLUID
KÄLTEMITTEL

R 134 a

CE 0062

6 - GROUPE - GROUP
GRUPPE

2

7 - CHARGES CIRCUIT A/B
RECHARGE CHARGE A/B
KREISLAUF A/B

51.00 Kg / 47.00 Kg

9 - FLUIDE D'INERTAGE
INERTING MEDIUM
NEUTRALISIERUNG-MEDIUM

23 - AZOTE - NITROGEN - STICKSTOFF

10 - PRESSION ADMISSIBLE RIN MAX
ALLOWABLE PRESSURE RIN MAX
ZULASSIGE RIN MAX - DRUCKE

21 - HAUTE PRESSION
HIGH PRESSURE
HOCHDRUCKSEITE
(PS) -1.0 / 21.00 bar

22 - BASSE PRESSION
LOW PRESSURE
NIEDERDRUCKSEITE
(PS) -1.0 / 21.00 bar

11 - TEMPERATURE ADMISSIBLE RIN MAX
ALLOWABLE TEMPERATURE RIN MAX
ZULASSIGE RIN MAX - TEMPERATUREN

(TS) -20 / 72 °C

-20 / 72 °C

12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS
PRESSURE SWITCH SETTING
DRUCKSCHWELLEN-EINSTELLUNG

16.0 bar

* bar

13 - PRESSION DE DECLENCHEMENT DES SOUPAPES
SAFETY RELIEF VALVE SETTING
SICHERHEITSENTWELPUNG - EINSTELLUNG

23.0 bar

23.0 bar

14 - PRESSION D'ESSAI D'ETANCHEITE DE L'UNITE
UNIT LEAK TEST PRESSURE
LECKTEST-DRUCK DES GERÄTS

15.0 bar

15 - TENSION
VOLTAGE
SPANNUNG

400 V 10 % 10 %

16 - PHASES
PHASES
PHASEN

17 - FREQUENCE
FREQUENCY
FREQUENZ

~ 50 Hz

18 - MAXIMALE
MAXIMUM AMPERE
MAXIMAL STROM

236.00

16 - PHASES
PHASES
PHASEN

19 - PUISSANCE ABSORBÉE MAX
MAX POWER INPUT
LEISTUNGSAUFNAHME

144.00 / * kW

20 - POIDS NET
NET WEIGHT
NETTOGEWICHT

2474 Kg

24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE
RUPTURE DISC SETTING
EINSTELLUNG DER RÜSSCHWEISSEN

* bar

* bar

Carrier

MANUFACTURED IN FRANCE BY
CARRIER SCS - 01120 MONTLUEL - FRANCE
A SUBSIDIARY OF CARRIER CORPORATION
SYRACUSE NEW YORK UNITED STATES OF AMERICA







