

Carrier 30 RW 080

Specifications

Производитель	Carrier
Тип	30 RW 080
Тип продукта	Water Cooled Chiller
кВт	80,0
Мощность, тонн	22,7
Хладагент	Freon
Тип хладагента	R407C
Масса	761
Sizes	2000x870x1800 mm (LxWxH)
Compressor(s) type & model	2x Performer SZ161T4VC
Display	Carrier Pro-Dialog Plus
Примечания	Y.o.b. 2007
Stock	1



Description

Used Carrier 30 RW 080

Used Carrier 30 RW 080 water cooled chiller on R407C. Complete with 2 Performer SZ161T4VC scroll compressors, plate heat exchanger as condenser with a water volume of 9 liter, plate heat exchanger as evaporator with a water volume of 9 liter and a Carrier Pro-Dialog Plus display.

*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform a industrial cleaning. if requested we can arrange your shipment.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER		12W712823	
2 - MODELE - MODEL MODELLNUMMER		30RW-080-0116-PEE--	
3 - VARIANTE VARIANT VARIANTE		30RW/30RWA	
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSDATUM UND DATUM		12/09/2007	
5 - FLUIDE - - MEDIUM KÄLMITTEL		R 407 C	
6 - GROUPE - - GROUP GRUPPE		2	
7 - CHARGES CIRCUIT A/B MEDIUM CHARGE A/B KREISLAUF A/B		11.0 Kg / * Kg	
9 - FLUIDE D'INERTAGE INERTING MEDIUM NEUTRALISIERUNG-MEDIUM		23 - AZOTE--NITROGEN--STICKSTOFF	
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULASSIGE MIN/MAX - DRUCK		21 - HAUTE PRESSION HIGH PRESSURE HOCHDRUCKSEITE	22 - BASSE PRESSION LOW PRESSURE NIEDERDRUCKSEITE
11 - TEMPERATURE ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULASSIGE MIN/MAX - TEMPERATUREN		(PS) -0.9 / 32.0 bar	-0.9 / 25.0 bar
12 - PRESSION DE DECLENCHEMENT DES PRESOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK		(TS) -20.0 / 72.0 °C	-20.0 / 46.0 °C
13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSENTLÜFT.-SOLLDRUCK		29.0 bar	* bar
14 - PRESSION D'ESSAI D'ETANCHETE DE L'UNITE UNIT LEAK TEST PRESSURE LEAKTEST-DRUCK DES GEBÄTS		* bar	25.0 bar
15 - TENSION VOLTAGE SPANNUNG		15.0 bar	15.0 bar
16 - PHASES PHASES PHASEN		400 V 10% 10%	3
17 - FREQUENCE FREQUENCY FREQUENZ		~ 50 Hz	18 - I MAXIMALE MAXIMUM AMP MAXIMAL STROM
19 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSAUFNAHME		51.6 / * A	31.5 / * kW
20 - POIDS NET NET WEIGHT NETTOGEWICHT		761 Kg	
24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISC SETTING EINSTELLDRUCK DER BERTSCHHEIBEN		* bar	* bar



