

Bitzer 4CC-9.2Y-40S Condensing unit

Specifications

Бренд	Bitzer
Тип	4CC-9.2Y-40S Condensing unit
Хладагент	Freon
kW at 0°C/+40°C	25,3
kW at -5°C/+40°C	21,1
кВт at -10°C/+40°C	17,4
кВт at -20°C/+40°C	11,4
кВт at -30°C/+40°C	7,0
кВт at -40°C/+40°C	3,8
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.20	
Маслоотделитель	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
Соленоидный клапан	✓
Панель управления	✓
m ³ / h	32,5 - 39,2
Примечания	Y.o.b. 2008
Condensing Unit	✓
Размеры	1450x1000x1300 mm (LxWxH)
Stock	1



Description

Used Bitzer 4CC-9.2Y-40S Condensing unit

Used Semi-hermetic Reciprocating Condensing unit on Freon. Complete with a Bitzer 4CC-9.2Y -40S semi-hermetic reciprocating compressor, Gökceler AC -RDG 200 A liquid receiver with a volume of 20 liter, condensor with 4 Ziehl-Abegg FE040 -4EK.2F.V7 fans 50 Hz - 0,31 kW - 1320 RPM - diameter 400 mm and pressure and safety switches. The compressor has a displacement of 32,5 m³/h at 1450 RPM and 39,2 m³/h at 1750 RPM.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and



arrange the logistics.





