

## Carrier 30 AWH 015 HD 9

### Specifications

|                            |                            |
|----------------------------|----------------------------|
| Производитель              | Carrier                    |
| Тип                        | 30 AWH 015 HD 9            |
| Тип продукта               | Heat pump                  |
| кВт                        | 15,0                       |
| Мощность, тонн             | 4,3                        |
| Хладагент                  | Freon                      |
| Тип хладагента             | R-410A                     |
| Pump                       | ✓                          |
| Масса                      | 113 kg                     |
| Sizes                      | 920x400x1340 mm<br>(LxWxH) |
| Compressor(s) type & model | Toshiba DA422A3F-27M       |
| Number of fans             | 2                          |
| Примечания                 | Y.o.b. 2021                |
| Stock                      | 1                          |



### Description

#### Used Carrier 30 AWH 015 HD 9

New Carrier 30 AWH 015 HD 9 heat pump on R-410A build in 2021. Complete with 1 Toshiba DA422A3F-27M scroll compressor, condenser with 2 fans, braced heat exchanger as evaporator, Grundfos UPML 25-105 water pump and a control cabinet. The unit comes with a EC declaration and has a energy label of A++ on a temperature of 55°C. Please notice that this unit is new but has some transport damage.

\*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your



Your partner for used commercial and  
industrial refrigeration equipment

---

shipment.



|                                                                                                         |            |                                                                                    |                  |                                                                                     |                                                                                     |                                                                                    |  |
|---------------------------------------------------------------------------------------------------------|------------|------------------------------------------------------------------------------------|------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--|
|                       |            |  |                  |  |                                                                                     |  |  |
| 30AWH015HD9                                                                                             |            |                                                                                    |                  |                                                                                     |                                                                                     | 210777400E                                                                         |  |
| 2021                                                                                                    | 210777400E | 6500 W                                                                             | 380-415V 50HZ 3N |  | IMAX 16A                                                                            | IPX4                                                                               |  |
|                      |            | ESTER_OIL_VG74                                                                     |                  |                                                                                     |  | 60 °C / 300 kPa                                                                    |  |
|                      |            | A7W45                                                                              | 3.3 COP          | 14.5 kW                                                                             | HI 4200 kPa<br>LO 1900 kPa                                                          |                                                                                    |  |
|                      |            | A7W35                                                                              | 4.2 COP          | 15 kW                                                                               | Refrigerant R-410A<br>GWP value 2088                                                |                                                                                    |  |
|                                                                                                         |            | A35W7                                                                              | EER              | 13 kW                                                                               | Refrigerant weight Factory: 3.38 Kg                                                 |                                                                                    |  |
|                                                                                                         |            | A35W18                                                                             | 3.81 EER         | 16 kW                                                                               | CO2 EQ Factory (t): 7.1                                                             |                                                                                    |  |
| Refrigerant Weight added on site (Kg):                                                                  |            |                                                                                    |                  |                                                                                     |                                                                                     | Refrigerant weight TOTAL:                                                          |  |
| CO2 EO on site (t):                                                                                     |            |                                                                                    |                  |                                                                                     |                                                                                     | CO2 EQ TOTAL (t):                                                                  |  |
| Contains fluorinated greenhouse gases covered by the Kyoto Protocol. Hermetically sealed system         |            |                                                                                    |                  |                                                                                     |                                                                                     |                                                                                    |  |
| Compañía Industrial de Aplicaciones Térmicas S.A. P.Ind. Llanos de Jara. 14550-Montilla Córdoba (SPAIN) |            |                                                                                    |                  |                                                                                     |                                                                                     |                                                                                    |  |

|                                     |                        |
|-------------------------------------|------------------------|
| CE                                  |                        |
| 33 Fan part number                  | C025223H01             |
| 34 Motor part number                | B036870H01             |
| 35 Input power supply               | 3P-230V AC             |
| 36 Frequency                        | 50Hz                   |
| 37 Electric Power                   | 0.15kW                 |
| 38 Reference speed                  | 847                    |
| 39 Overall efficiency               | n=29.1%                |
| 40 Measurement, Efficiency category | (A <sub>static</sub> ) |
| 41 Target Efficiency grade          | N(2015)40              |
| 42 Efficiency grade                 | N=40.6                 |
| 43 VSD installed                    | Yes                    |
| According to EU Regulation 327/2011 |                        |
| 00PSG002168000                      |                        |





