

Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

Specifications

Бренд	Bitzer
Тип	4TCS-12.2Y-40P (x2) Condensing unit
Хладагент	Freon
kW at 0°C/+40°C	64,2
kW at -5°C/+40°C	52,1
кВт at -10°C/+40°C	41,8
кВт at -20°C/+40°C	25,7
кВт at -30°C/+40°C	14,5
На стальной раме	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.70	
Маслоотделитель	✓
Система маслоуравнивания	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
Панель управления	✓
m3 / h	50 Hz - 82,6 m³/h / 60 Hz - 98,8 m³/h
Примечания	Y.o.b. 2008
Condensing Unit	✓
Размеры	3140x2250x1610 mm (LxWxH)
Stock	1



Description

Used Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

Used Profroid GC4/CCR2SH4TCS12 ZC/C4AH 2MD3 condensing unit on Freon. Complete with 2 Bitzer 4TCS-12.2Y-40P semi-hermetic reciprocating compressors, condenser with 2 fans, Tecnac RH-273-70 liquid receiver with a volume of 70 liter, oil separator, liquid line filter drier, Danfoss VLT FC-103P18KT4P55H1 frequency regulator, Danfoss AKD102P7K5T4E20H drive and a control cabinet with 2 Danfoss controllers. The compressors have a total displacement of 82,6 m³/h at 50 Hz & 98,8 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist



in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.









