

Sabroe TSMC 188 (x3) Installation

Specifications

Бренд	Sabroe
Тип	TSMC 188 (x3) Installation
Хладагент	NH 3 (ammonia)
кВт at -10°C/+40°C	2415,9
кВт at -20°C/+40°C	1637,1
кВт at -30°C/+40°C	1030,5
кВт at -40°C/+40°C	611,1
Электродвигатель	Schorch KA4355M-KZ81T-
Specs	Z - 50/60 Hz - 120/160 kW - 740/993 RPM
Разгруженный старт	✓
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.6830	
Маслоотделитель	✓
Смотровое стекло	✓
Соленоидный клапан	✓
m3 / h	3.849
Примечания	Y.o.b. 2003
Package / Rack	✓
Stock	1



Description

Used Sabroe TSMC 188 (x3) Installation

Used cooling installation with 3 Sabroe TSMC 188 reciprocating compressors on NH3 (Ammonia). Each compressor is complete with a Schorch KA4355M-KZ81T-Z electric motor - 50 Hz - 120/160 kW - 740/993 RPM, Sabroe OVUR 6006 oil separator, Sabroe OVUR 3211D oil separator and pressure and safety switches/gauges. The compressors have a displacement of 3.849 m³/h. The compressors always have been running on low speeds.

The installation includes a Zeta separator with a volume of 6340 liter and 2 Hermetic CAM 1/4 NH3 pumps and a second Zeta separator with a volume of 11.200 liter and 3 Hermetic CAMR 2/3 NH3 pumps.

Further the set comes with a VEB K 4.2.29 NH3 receiver with a volume of 6830 liter. Dimensions: 6440x1300x1450 mm (LxWxH).

This set comes with certificates and has the following capacities:

-10°C/+40°C: 2415,9 kW
-20°C/+40°C: 1637,1 kW
-30°C/+40°C: 1030,5 kW
-40°C/+40°C: 611,1 kW

We can deliver this installation with suitable condensers and evaporators. Please feel free too contact us for more information!

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase.
*If requested we are happy to arrange your shipment.



















