

DWM D3DS5-150X-AWM/D (x1) & 3DS5-150X-AWM/D (x1)

Specifications

Бренд	DWM
Тип	D3DS5-150X-AWM/D (x1) & 3DS5-150X-AWM/D (x1)
Хладагент	Freon
kW at 0°C/+40°C	84,7
kW at -5°C/+40°C	69,6
кВт at -10°C/+40°C	56,6
кВт at -20°C/+40°C	36,1
кВт at -30°C/+40°C	21,2
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Прессостаты конденсатора	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.90	
Маслоотделитель	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
m ³ / h	99,8
Package / Rack	✓
Размеры	2250x900x1450 mm (LxWxH)
Stock	1



Description

Used DWM D3DS5-150X-AWM/D (x1) & 3DS5-150X-AWM/D (x1)

Used DWM D3DS5-150X-AWM/D (x1) & 3DS5-150X-AWM/D (x1) tandem setup semi-hermetic reciprocating compressor on Freon. Complete with an ESK Schultze OS-35H oil separator, Güntner liquid receiver with a volume of 90 liter, liquid line filter drier, pressure and safety switches/gauges. The compressors together have a displacement of 99,8 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.





