

Mycom N6WA-BB

Specifications

Бренд	Mycom
Тип	N6WA-BB
Хладагент	NH 3 (ammonia)
kW at 0°C/+40°C	147,8*
kW at -5°C/+40°C	129,2*
кВт at -10°C/+40°C	112,3*
кВт at -20°C/+40°C	67,8*
кВт at -30°C/+40°C	44,1*
кВт at -40°C/+40°C	27,4*
Электродвигатель	50/60 Hz - 75/85 kW -
Specs	1480/1780 RPM
Разгруженный старт	✓
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Маслоотделитель	✓
Смотровое стекло	✓
m ³ / h	281 m ³ /h
Примечания	Y.o.b. 2010
Примечания	*Capacity based on a condensing temperature of 10°C
Размеры	2150x1250x2230 mm (LxWxH)
Stock	2



Description

Used Mycom N6WA-BB

Used Mycom N6WA-BB reciprocating compressor on R717 (Ammonia). Complete with WEG 280SM4 electric motor - 50/60 Hz - 75/85 kW - 1480/1780 RPM, Mayekawa OSF200/26/52-PM4 oil separator, pressure and safety switches/gauges. The compressor has a displacement of 281 m³/h. Capacity based on a condensing temperature of 10°C.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





