

Howden MK 4C/WRVB255/22036/269

Specifications

Бренд	Howden
Тип	MK 4C/WRVB255/22036/269
Хладагент	NH 3 (ammonia)
kW at -5°C/+40°C	1900,0 (-10°C/-10°C)
кВт at -10°C/+40°C	1750,0 (-10°C/+10°C)
кВт at -20°C/+40°C	1020,0 (-20°C/+10°C)
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Маслоотделитель	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
Package / Rack	✓
Размеры	4550x1260x2200 mm (LxWxH)
Stock	1



Description

Used Howden MK 4C/WRVB255/22036/269

Used Howden MK 4C/WRVB255/22036/269 open-drive screw compressor unit on NH3 (Ammonia). Complete with a Leroy Somer P P315MU-T electric motor - 50 Hz - 160/110 kW - 2980/1480 RPM, Howden T 61 oil separator with a volume of 510 liters, Hans Güntner GmbH B219/3000/1 W shell and tube heat exchanger, oil cooler, Howden 450 liquid line filter drier, Mycom M50P-M oil pump with F-part FMS90L1-2 electro motor - 50/60 Hz - 2,2/2,64 kW - 2840/3400 RPM and pressure safety switches/gauges.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has



passed our extensive test. Warranty
and industrial cleaning are included in
your purchase. *If requested we are
happy to arrange your shipment.









