

Güntner GFHV FD 090.2NF/12E-52

Specifications

Производитель	Güntner
Тип	GFHV FD 090.2NF/12E-52
Тип продукта	Drycooler
кВт	111,5*
К-во вентиляторов	2
Скорость вращения вентиляторов	830
Хладагент	Glycol
Поток воздуха м³/час	41.100
диаметр вентиляторов	910 mm
Ø	
поверхность (m2)	319,4
Объем трубки	60,8 dm³
Размеры	4270x1105x1840 mm (LxWxH)
Примечания	Y.o.b. 2023
Remarks	*Capacity explained in the description
Stock	1



Description

Used Güntner GFHV FD 090.2NF/12E-52

New Güntner GFHV FD 090.2NF/12E-52 drycooler built in 2023. Complete with 2 EBМ-Papst S3G910-CS35-68 fans - 50/60 Hz - 1,55 kW - 830 RPM - diameter 910 mm and a total airflow of 41.100 m³/h.

*Capacity based on the following:
 Air inlet/outlet temperature: 25°C/33,2°C
 Medium Inlet/outlet temperature: 40°C/35°C
 Volume flow: 20,9 m³/h
 Medium: Glycol 34%.

Capacity of 216,8 kW based on the following:
 Air inlet/outlet temperature: 25°C/40,9°C

Medium Inlet/outlet temperature:
60°C/40°C

Volume flow: 10,2 m³/h

Medium: Glycol 34%.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning. on demand, we can arrange your shipment.





