

Güntner GFH 102C/2*3 S (D)-F4 /3

Specifications

Производитель	Güntner
Тип	GFH 102C/2*3 S (D)-F4 /3
Тип продукта	Drycooler
кВт	250,6
К-во вентиляторов	6
Скорость вращения вентиляторов	430/310
Хладагент	Glycol
Поток воздуха м³/час	84.500
диаметр вентиляторов	1000 mm
Ø	
поверхность (m2)	1190,5
Объем трубки	221 dm³
Размеры	7260x2400x1500 mm (LxWxH)
Stock	4



Description

Used Güntner GFH 102C/2*3 S (D)-F4 /3

Used Güntner GFH 102C/2*3S (D)-F4 /3 drycooler. Complete with 6 Ziehl-Abegg FE100-NDS.6N.V7 fans - 50 Hz - 0,50/0,19 kW - 430/310 RPM - diameter 1000 mm and a total airflow of 84.500 m³/h.

*Capacity based on the following:

Air inlet/outlet temperature:
25°C/33,9°C.

Medium Inlet/outlet temperature:
40°C/35°C.

Volume flow: 47,1 m³/h.

Medium: Glycol 34%.

Capacity of 625,1 kW based on the following:

Air inlet/outlet temperature:
25°C/47,3°C.

Medium Inlet/outlet temperature:
60°C/40°C.

Volume flow: 29,3 m³/h.

Medium: Glycol 34%.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning. on demand, we can arrange your shipment.





