

# Coolers & Condensers Ltd VF 44-8R6mm-SP

## Specifications

|                                   |   |
|-----------------------------------|---|
| Производитель                     | Coolers & Condensers Ltd                                  |
| Тип                               | VF 44-8R6mm-SP  |
| кВт                               | 91,1  |
| Хладагент                         | Freon   |
| К-во вентиляторов                 | 2   |
| Расстояние между ламелями, мм     | 6   |
| Оттайка                           | Electric  |
| Поток воздуха м <sup>3</sup> /час | *Capacity based on an airflow of 40.000 м <sup>3</sup> /h |
| Размеры                           | 3320x1300x2470 mm (LxWxH)                                 |
| Stock                             | 1   |





## Description

### Used Coolers & Condensers Ltd VF 44-8R6mm-SP

Used Coolers & Condensers VF 44-8R6mm-SP Freon evaporator with electric defrost. Complete with 2 fans that have are driven by a Woods F22-100L2-4 electric motor: 50/60 Hz - 3,2/3,4 kW - 6,6/6,4 A - diameter 800 mm. \*Capacity based on an airflow of 40.000 м<sup>3</sup>/h.

\*All components of this used evaporator will be tested in good working, leak-free condition (electro engines, coils, bearings). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. Also, we can arrange your shipment.



|  |       |   |            |
|--|-------|---|------------|
| Model VF 44-8R6mm-SP   |       | Serial No. SOP0036745   |            |
| Medium R449A   |       | Date:   |            |
| Max Pressure 27.00 Barg  |       | Test No.:   |            |
| Min Pressure -1 Barg   |       | Max temp : 100 C Min temp : -50 C   |            |
| FAN MOTORS FLC / PHASE(in Amps)  |       |   |            |
| No Off   | Volts | Phase   | kW         |
| 2  | 415   | 3   | 3.2        |
|  |       |   | Hz         |
|  |       |   | 50         |
|  |       |   | 1          |
|  |       |   | 2          |
|  |       |   | 3          |
|  |       |   | 6.75       |
|  |       |   | 6.75       |
|  |       |   | 6.75       |
| DEFROST FLC / PHASE(in Amps)   |       |   |            |
|  | Volts | Phase   | Watts (kW) |
| Coil   | 415   | 3   | 26.12      |
|  |       |   | 37.86      |
|  |       |   | 37.86      |
| Tray   | 415   | 3   | 3.73       |
|  |       |   | 5.41       |
|  |       |   | 5.41       |
|  |       |   | 5.41       |
| Perifs   |       |   |            |
| <br>12 Brunel Way<br>Segensworth East Ind Est<br>Farnham, Hampshire PO15 6TJ<br>United Kingdom<br>tel: 01480 855533 |       | Made In The UK<br> |            |

