

Bitzer 4N-20.2 Y (x3)

Specifications

Бренд	Bitzer
Тип	4N-20.2 Y (x3)
Хладагент	Freon
kW at 0°C/+40°C	137,4
kW at -5°C/+40°C	114,3
кВт at -10°C/+40°C	93,9
кВт at -20°C/+40°C	61,2
кВт at -30°C/+40°C	37,2
кВт at -40°C/+40°C	19,2
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.7,4	
Маслоотделитель	✓
Система маслоуравнивания	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
m ³ / h	50 Hz - 168,3 m ³ /h & 60 Hz - 203,1 m ³ /h
Package / Rack	✓
Размеры	2115x1500x1200 mm (LxWxH)
Stock	1



Description

Used Bitzer 4N-20.2 Y (x3)

Used Bitzer 4N-20.2 Y (x3) semi-hermetic reciprocating compressors on Freon. Complete with a Carly HCYR 81 oil receiver, Temprite 926 L oil separator, pressure and safety switches/gauges, oil level system AC&R and a filter drier. The compressors have a total displacement of 168,3 m³/h at 50 Hz & 203,1 m³/h at 60 Hz. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.





