

Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit

Specifications

| | |
|-----------------------------|--|
| Бренд | Bitzer |
| Тип | 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit |
| Хладагент | Freon |
| kW at 0°C/+40°C | 82,3 |
| kW at -5°C/+40°C | 65,5 |
| кВт at -10°C/+40°C | 51,4 |
| кВт at -20°C/+40°C | 29,4 |
| Прессостаты | ✓ |
| Манометры | ✓ |
| Маслоотделитель | ✓ |
| Система маслоуравнивания | ✓ |
| Фильтр-осушитель | ✓ |
| Смотровое стекло | ✓ |
| Панель управления | ✓ |
| m ³ / h | 161,1 |
| Примечания | Y.o.b. 2014 |
| Package / Rack | ✓ |
| Размеры | 2300x1400x1400 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit

Used Rivacold RV4C1103-1 compressor unit on Freon. Complete with a Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) semi-hermetic reciprocating compressors, Ocs cold OCS-08 oil reservoir, Henry Technologies S-1901-CE oil separator, pressure and safety switches/gauges and a control cabinet with a Carel pR100 controller and Carel display. The compressors have a total displacement of 161,1 m³/h. The capacity is based on the use of Freon type: R134A.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all



equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.









