

Bitzer 4H-25.2

Specifications

| | |
|--------------------|---------------------------|
| Бренд | Bitzer |
| Тип | 4H-25.2 |
| Хладагент | Freon |
| kW at 0°C/+40°C | 59,4 |
| kW at -5°C/+40°C | 49,4 |
| кВт at -10°C/+40°C | 40,6 |
| кВт at -20°C/+40°C | 26,4 |
| кВт at -30°C/+40°C | 15,9 |
| кВт at -40°C/+40°C | 8,3 |
| kW at -45°C/+40°C | 5,4 |
| Разгруженный старт | ✓ |
| Смотровое стекло | ✓ |
| Соленоидный клапан | ✓ |
| m ³ / h | 73,6 |
| Масса | 203 |
| Размеры | 720x460x850 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4H-25.2

Used Bitzer 4H-25.2 semi-hermetic reciprocating compressor on Freon. Complete with unloaded start, capacity control and a sight glass. The compressor has a displacement of 73,6 m³/h.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.

