

# Bitzer 4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1)

## Specifications

Бренд	Bitzer
Тип	4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1)
Хладагент	Freon
kW at 0°C/+40°C	107,8
kW at -5°C/+40°C	89,3
кВт at -10°C/+40°C	73,5
кВт at -20°C/+40°C	47,6
кВт at -30°C/+40°C	28,7
кВт at -40°C/+40°C	14,9
kW at -45°C/+40°C	9,8
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Маслоотделитель	✓
Система маслоуравнивания	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
m <sup>3</sup> / h	136,6
Примечания	Y.o.b. 2001



Package / Rack	✓
Размеры	2900x1000x1690 mm (LxWxH)
Stock	1

## Description

### **Used Bitzer 4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1)**

Used Bitzer 4FC-5.2 Y (x1) & 2DC-3.2 Y (x2) & 2CC-4.2 Y (x1) & 4DC-7.2 Y (x1) & 4P-15.2 Y (x1) semi-hermetic reciprocating compressors rack on Freon. Complete with a x1 Bitzer FS 302 and x1 Bitzer FS 562 liquid receivers, x2 AC&R S-9108U oil reservoirs, x1 AC&R S-5188 and x1 AC&R S-5192 oil separators, pressure and safety switches and a liquid line filters drier. The compressors have a total displacement of 136,6 m<sup>3</sup>/h at 50 Hz and 163,1 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.









