

# Bitzer 4G-30.2

## Specifications

|                     |                           |
|---------------------|---------------------------|
| Бренд               | Bitzer                    |
| Тип                 | 4G-30.2                   |
| Хладагент           | Freon                     |
| kW at 0°C/+40°C     | 68,6                      |
| kW at -5°C/+40°C    | 57,0                      |
| кВт at -10°C/+40°C  | 47,0                      |
| кВт at -20°C/+40°C  | 30,7                      |
| кВт at -30°C/+40°C  | 18,6                      |
| кВт at -40°C/+40°C  | 9,8                       |
| Управление          | ✓                         |
| производительностью |                           |
| Смотровое стекло    | ✓                         |
| m <sup>3</sup> / h  | 84,6                      |
| Размеры             | 740x470x430 mm<br>(LxWxH) |
| Stock               | 1                         |



## Description

### Used Bitzer 4G-30.2

Used Bitzer 4G-30.2 semi-hermetic reciprocating compressor on Freon with a displacement of 84,6 m<sup>3</sup>/h. &lt;br&gt;  
 \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.  
 \*Optional we can also perform a new paint job and arrange the logistics.

