

Bitzer 2CC-4.2Y-40S Condensing unit

Specifications

Бренд	Bitzer
Тип	2CC-4.2Y-40S Condensing unit
Хладагент	Freon
kW at 0°C/+40°C	12,7
kW at -5°C/+40°C	10,5
кВт at -10°C/+40°C	8,7
кВт at -20°C/+40°C	5,6
кВт at -30°C/+40°C	3,4
кВт at -40°C/+40°C	1,8
На стальной раме	✓
Прессостаты	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.13	
Маслоотделитель	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
m ³ / h	16,2 m ³ /h at 50 Hz & 19,6 m ³ /h at 60 Hz
Примечания	Y.o.b. 2005
Condensing Unit	✓
Размеры	1350x720x850 mm (LxWxH)
Stock	1



Description

Used Bitzer 2CC-4.2Y-40S Condensing unit

Used Bitzer 2CC-4.2Y-40S condensing unit on Freon. Complete with a Bitzer 2CC-4.2Y-40S semi-hermetic reciprocating compressor, condenser with 1 Ziehl-Abegg FB045-4EK.4I.6P fan - 50/60 Hz - 0,48/0,73 kW - 1340/1530 RPM - diameter 450 mm, Bitzer FS126 liquid receiver with a volume of 13 liter, oil separator, liquid line filter drier, pressure and safety switches and a control cabinet. The compressor has a displacement of 16,2 m³/h at 50 Hz & 19,6 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new



paint job and arrange the logistics.





