

Mycom FM160L-L

Specifications

Бренд	Mycom
Тип	FM160L-L
Хладагент	NH 3 (ammonia)
кВт at +10°C/+40°C	835,4
kW at 0°C/+40°C	579,6
kW at -5°C/+40°C	475,6
кВт at -10°C/+40°C	385,6
кВт at -20°C/+40°C	242,7
кВт at -30°C/+40°C	140,7
Электродвигатель	50/60 Hz - 132/152 kW -
Specs	2945/3538 RPM
Разгруженный старт	✓
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Маслоотделитель	✓
Смотровое стекло	✓
Панель управления	✓
Примечания	Y.o.b. 2008
Масса	3300
Stock	1



Description

Used Mycom FM160L-L

Used Mycom / Mayekawa FM160L-L screw compressor skid on NH3 (Ammonia). Complete with a Leroy Somer PLS280MC-T electric motor - 50/60 Hz - 132/152 kW - 2945/3538 RPM, Mayekawa HS 6023 oil separator with a volume of 700 liter, Mayekawa OC-15245-V oil cooler, 2 Mayekawa OFC 50 oil filter, pressure and safety switches/gauges and a control cabinet with a Mycom MYPRO-CP3 controller.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.







