

# Gram HC 6075

## Specifications

Бренд	Gram
Тип	HC 6075
Хладагент	NH 3 (ammonia)
kW at 0°C/+40°C	81,4*
kW at -5°C/+40°C	69,8*
кВт at -10°C/+40°C	52,3*
кВт at -20°C/+40°C	31,4*
кВт at -30°C/+40°C	12,2*
Разгруженный старт	✓
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Маслоотделитель	✓
Смотровое стекло	✓
Соленоидный клапан	✓
m <sup>3</sup> / h	222
Примечания	*Capacity based on a condensing temperature of 25°C
Размеры	1600x900x900 mm (LxWxH)
Stock	1



## Description

### Used Gram HC 6075

Used Gram HC 6075 reciprocating compressor on NH<sub>3</sub> (Ammonia). Complete with a Leroy Somer PLS200M-T electric motor - 50/60 Hz - 37/42 kW - 1435/1745 RPM, Gram oil separator, pressure and safety switches/gauges. The compressor has a displacement of 222 m<sup>3</sup>/h at 1850 RPM. Capacity based on a condensing temperature of 25°C. Used Grasso RC 612 single stage reciprocating compressor on NH<sub>3</sub> (Ammonia). Complete with a ABB Motors M2BA 315SMB 4 B3 electromotor - 50/60 Hz - 132/150 kW - 1487/1785 RPM, oil separator with a volume of 120 liters, pressure safety switches/gauges and sight glass. The compressor has a displacement of 798,0 m<sup>3</sup>/h.





