

# Bitzer 4N.2

## Specifications

Бренд	Bitzer
Тип	4N.2
Хладагент	Freon
kW at 0°C/+40°C	47,9
kW at -5°C/+40°C	39,9
кВт at -10°C/+40°C	32,9
кВт at -20°C/+40°C	21,7
кВт at -30°C/+40°C	13,4
кВт at -40°C/+40°C	7,5
kW at -45°C/+40°C	5,2
Разгруженный старт	✓
Управление	✓
производительностью	
Система	✓
маслоуравнивания	
Соленоидный клапан	✓
m <sup>3</sup> / h	27,0 m <sup>3</sup> /h at 700 RPM & 67,7 m <sup>3</sup> /h at 1750 RPM
Масса	170
Размеры	1060x550x500 mm (LxWxH)
Stock	1



## Description

### Used Bitzer 4N.2

Used Bitzer 4N.2 open-type reciprocating compressor on Freon. Complete with a Leroy-Somer P160L-T electric motor - 50 Hz - 15 kW - 1435 RPM, capacity control, unloaded start and an oil level regulator. The compressor has a displacement of 27 m<sup>3</sup>/h at 700 RPM & 67,7 m<sup>3</sup>/h at 1750 RPM.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.



