

Bitzer HSN 7471-75-40P

Specifications

| | |
|--------------------------|------------------------------|
| Бренд | Bitzer |
| Тип | HSN 7471-75-40P |
| Хладагент | Freon |
| Refrigerant type | R404A |
| кВт at -20°C/+40°C | 120,3 |
| кВт at -30°C/+40°C | 82,9 |
| кВт at -40°C/+40°C | 54,5 |
| kW at -45°C/+40°C | 43,0 |
| Разгруженный старт | ✓ |
| Управление | ✓ |
| производительностью | |
| На стальной раме | ✓ |
| Прессостаты | ✓ |
| Манометры | ✓ |
| Жидкостный ресивер | ✓ |
| Жидкостный ресивер л.112 | |
| Маслоотделитель | ✓ |
| Фильтр-осушитель | ✓ |
| Смотровое стекло | ✓ |
| Соленоидный клапан | ✓ |
| m ³ / h | 250 |
| Примечания | Y.o.b. 2011 |
| Размеры | 1900x1050x2030 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer HSN 7471-75-40P

Used Bitzer HSN7471-75-40P semi-hermetic screw compressor Freon on steel base frame. Complete with Bitzer F1202N liquid receiver, Bitzer OA1954 oil separator, Gea GBS 700M-20 brazed heat exchanger as economizer, Gea GBS 700M-44 brazed heat exchanger for heat recovery, pressure and safety switches/gauges and a liquid line filter drier. The compressor has a displacement of 250 m³/h at 2900 RPM and 300 m³/h at 3500 RPM. The capacities are with a economizer.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





