

Bitzer BHS-1102

Specifications

| Бренд | Bitzer |
|----------------------------|--|
| Тип | BHS-1102 |
| Хладагент | Freon |
| кВт at -10ºC/+40ºC | 22,8 |
| кВт at -20ºC/+40ºC | 14,6 |
| кВт at -30ºC/+40ºC | 8,86 |
| кВт at -40ºC/+40ºC | 4,77* |
| Разгруженный старт | / |
| Просседствен | |
| Прессостаты | √ |
| Примечания | # *Can only run -40C |
| | • |
| | # *Can only run -40C |
| Примечания | # *Can only run -40C with head fan |
| Примечания | # *Can only run -40C with head fan R404a - R22 or other |
| Примечания Примечания | # *Can only run -40C with head fan R404a - R22 or other freon types |
| Примечания Примечания | # *Can only run -40C with head fan R404a - R22 or other freon types 700x440x440 mm |



Description

Used Bitzer BHS-1102

Used Bitzer BHS-1102 freon compressor, complete with unloaded start and pressure safety switches. This unit has a cooling capacity of 22,8 kW at $-10^{\circ}\text{C}/+40^{\circ}\text{C}$.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment







info@hosbv.com