

Bitzer 4H.2

Specifications

Бренд	Bitzer
Тип	4H.2
Хладагент	Freon
kW at 0°C/+40°C	54,8
kW at -5°C/+40°C	45,7
кВт at -10°C/+40°C	37,7
кВт at -20°C/+40°C	24,8
кВт at -30°C/+40°C	15,3
кВт at -40°C/+40°C	8,4
Электродвигатель	15 kW at 1460 RPM
Specs	
Разгруженный старт	✓
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
Панель управления	✓
Примечания	# // Electromotor: 15 kW at 1460 RPM // Pulley EM: 200 mm / Pulley compr.: 220 mm
Примечания	R404a - R22 or other freon types
Размеры	1650x1200x2200 mm (LxWxH)



Stock

1

Description

Used Bitzer 4H.2

Used Bitzer 4H.2 freon compressor, complete with unloaded start, pressure safety switches, pressure gauges, liquid receiver, liquid line filter drier, sight glass and control panel. This unit has a cooling capacity of 54,8 kW at 0°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.





