

Bitzer 6F.2 (x3)

Specifications

Бренд	Bitzer
Тип	6F.2 (x3)
Хладагент	Freon
кВт at +10°C/+40°C	497,7*
kW at 0°C/+40°C	382
kW at -5°C/+40°C	317,1
кВт at -10°C/+40°C	260,9
кВт at -20°C/+40°C	170
кВт at -30°C/+40°C	103,2
кВт at -40°C/+40°C	55,5
Электродвигатель	37
Spacs	
Разгруженный старт	✓
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.30	
Маслоотделитель	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
Панель управления	✓



	1475 RPM // DX Unit
Примечания	#4046 Cap. R22, based on freon type R32 //
Package / Rack	Electromotor: 37 kW at
Размеры	2900x1500x1750 mm (LxWxH)
Stock	1

Description

Used Bitzer 6F.2 (x3)

Used Bitzer 6F.2 (x3) freon compressor rack, complete with unloaded start, capacity control, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, sight glass, control panel and liquid receiver with a volume of 30 liters.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.









