

Bitzer 4G-30.2 (x1) / 4G.2 (x2)

Specifications

Бренд	Bitzer
Тип	4G-30.2 (x1) / 4G.2 (x2)
Хладагент	Freon
kW at -5°C/+40°C	201,4
кВт at -10°C/+40°C	165,5
кВт at -20°C/+40°C	107,9
кВт at -30°C/+40°C	65,5
Электродвигатель	22
Specs	
Разгруженный старт	✓
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.224	
Отделитель жидкости	✓
Маслоотделитель	✓
Система	✓
маслоуравнивания	
Фильтр-осушитель	✓
Смотровое стекло	✓
Примечания	y.o.b. 2005 (4G-30.2) / 2008, 2002 (4G.2) // Electromotor: 22 kW at 1445 RPM



Примечания	R404a – R22 or other freon types
Package / Rack	✓
Размеры	2900x2150x1800 mm (LxWxH)
Stock	1

Description

Used Bitzer 4G-30.2 (x1) / 4G.2 (x2)

Compressor unit Bitzer 4G-30.2 (x1) / 4G.2 (x2) with 2 Electromotor Leroy Somer P180M.T (22 kW at 1445 RPM). This used compressor unit has the following components: Liquid Receiver Bitzer F2701N, Oil Separator and more.
*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.





