

Bitzer 4HE-15Y-40P + 4NES-12Y-40P (x2) + 2KSL-1K-40S (x2) + 44VES-20Y-40P CO2/Freon system

Specifications

Бренд	Bitzer
Тип	4HE-15Y-40P + 4NES-12Y-40P (x2) + 2KSL-1K-40S (x2) + 44VES-20Y-40P CO2/Freon system
Хладагент	CO2
кВт at -10°C/+40°C	83,8
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.80	
Маслоотделитель	✓
Система маслоуравнивания	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
Панель управления	✓
Примечания	y.o.b. 2014
Package / Rack	✓
Размеры	3510x1400x2000 mm
Stock	1



Description

Used Bitzer 4HE-15Y-40P + 4NES-12Y-40P (x2) + 2KSL-1K-40S (x2) + 44VES-20Y-40P CO2/Freon system

Used Bitzer CO2/Freon installation with a cool/freeze and heat pump system. Cool system: (1x) Bitzer 4HE-15Y-40P (2x) Bitzer 4NES-12Y-40P capacity 84 kW (-10/+40°C) 70 Hz - R134A. Freeze system: (2x) Bitzer 2KSL-1K-40S capacity 11 kW (-33/-5°C) 60 Hz - R744. Heatpump system: Bitzer 44VES-20Y-40P capacity 56 kW (+10/+48°C) 70 Hz - R134A with air purger. Emergency cooling (1x) Bitzer 4FES-3Y-40S capacity 0,39 kW (+10/+40°C).

*Why choose for HOSBV? Were not only the largest used refrigeration specialist



Your partner for used commercial and industrial refrigeration equipment

in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also arrange the logistics.







