

### Mycom 200 VSD 5.8

### **Specifications**

Brand	Mycom
Туре	200 VSD 5.8
Refrigerant	NH 3 (ammonia)
kW at -10°C/+40°C	508,7
kW at -20°C/+40°C	366,2
kW at -30ºC/+40ºC	221,3
kW at -40°C/+40°C	115,8
kW at -45°C/+40°C	75,2
Electromotor Specs	Mayekawa 50Hz / 160
	kW / 2970 RPM
On steel base frame	1
On steel base frame Pressure gauges	✓ ✓
Pressure gauges	
Pressure gauges Hp/Lp/Op	✓ ·
Pressure gauges Hp/Lp/Op Oil separator	<i>y</i>
Pressure gauges Hp/Lp/Op Oil separator Sight Glass	/ /
Pressure gauges Hp/Lp/Op Oil separator Sight Glass Weight in kg.	✓ ✓ 6700 approx
Pressure gauges Hp/Lp/Op Oil separator Sight Glass Weight in kg. Package / Rack	✓ ✓ 6700 approx
Pressure gauges Hp/Lp/Op Oil separator Sight Glass Weight in kg. Package / Rack	✓ ✓  6700 approx ✓  3300x1500x2000 mm



### **Description**

#### Used Mycom 200 VSD 5.8

Used Mycom/Mayekawa 200 VSD 5.8 screw compressor package. contaiing the following elements: Electro motor Mayekawa 50Hz with 160 kW at 2970 RPM. Oil separator 1340 ltr, shell and tube oil cooler shell side 48 ltr and tube side 36 ltr with oil filter and pump. \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. \*Optionally we can also perform a new paint job and arrange the logistics.



# Your partner for used commercial and industrial refrigeration equipment















# Your partner for used commercial and industrial refrigeration equipment













# Your partner for used commercial and industrial refrigeration equipment









