

# Carrier 30 HXC 370

## Specifications

Brand	Carrier
Type	30 HXC 370
Product type	Water Cooled Chiller
Capacity kW	1295,9
Capacity Tons	368,5
Refrigerant	Freon
Refrigerant Type	R134a
Weight in kg.	6.165
Sizes	5700x950x2100 mm (LxWxH)
Compressor(s) type & model	Carlyle 06NW2300S5EA-A00 (x4)
Stock	1



## Description

### Used Carrier 30 HXC 370

Used Carrier 30HXC370--0043-AEE watercooled chiller. Complete with 4 Carlyle 06NW2300S5EA screw compressors. Shell & tube evaporator/exchanger 229 Liter. Carrier 09HX2137 condensor containing a volume of 251 liter. 2 Oil separators and multiple liquid line filter driers. Mentioned capacity is with the evaporator water temperature (in/out) of +12°C/+7°C and condenser water temperature (in/out) of +30°C/+35°C. \*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning. Also, we can arrange your shipment.



N° DE MODELE-MODEL N - TYP-		30HXC370--0043-AEE--	
N° DE SERIE-SERIAL N - FABR N°:		12F813014	
ANNEE-YEAR-BAUJAHR-		1998	
PRESSION MAX. FONCTION- COTE H.P-MAX. OPERATING PRESS- HIGH SIDE ZULÄSSIGER BETRIEBSÜBERDRUCK - HOCHDRUCKSEITE		24,50 bar	
PRESSION MAX. FONCTION- COTE B.P-MAX. OPERATING PRESS- LOW SIDE ZULÄSSIGER BETRIEBSÜBERDRUCK - NIEDRDRUCKSEITE		24,50 bar	
FLUIDE - REFRIGERANT - KÄLTEMITTEL		R 134A	
CHARGE CIRCUIT 1 FÜLLMENG KREISLAUF 1	110,00 kg	CHARGE CIRCUIT 2 FÜLLMENG KREISLAUF 2	120,00 kg
TENSION VOLTAGE SPANNUNG	400 V	FREQUENCE CYCLES FREQUENZ	50 Hz
I. NOMINALE NOM. AMPS NENNSTROM	300,0 A	PUISSANCE ABSORBEE POWER INPUT LEISTUNGS-AUFNAHME	184,0 kW
POIDS NET NET WEIGHT NETTOGEWICHT	5529 kg	DRUCKBEH. GRUPPE B.V	/
 <p>MANUFACTURED IN FRANCE BY CARRIER s.a. 01120-MONTLUEL-FRANCE</p>			
A SUBSIDIARY OF CARRIER CORPORATION SYRACUSE NEW YORK UNITED STATES OF AMERICA			













