

## Sabroe SAB 128 HF MK2 man VI

### **Specifications**

Brand	Sabroe
Туре	SAB 128 HF MK2 man VI
Refrigerant	NH 3 (ammonia)
kW at +10°C/+40°C	610,3
kW at 0°C/+40°C	423,2
kW at -5°C/+40°C	347,9
kW at -10°C/+40°C	283,2
kW at -20°C/+40°C	214,8
kW at -30°C/+40°C	134,7
kW at -40°C/+40°C	77,8
Electromotor Specs	50 Hz - 49,5 kW - 2950
	RPM
Capacity Control	RPM ✓
Capacity Control On steel base frame	
	/
On steel base frame	/
On steel base frame Oil separator	/ /
On steel base frame Oil separator Sight Glass	/ / / /
On steel base frame Oil separator Sight Glass Control panel	/ / / / / /
On steel base frame Oil separator Sight Glass Control panel m3 / h	<ul><li>/</li><li>/</li><li>/</li><li>/</li><li>/</li><li>455,0</li></ul>
On steel base frame Oil separator Sight Glass Control panel m3 / h	<ul> <li>/</li> <li>/</li> <li>/</li> <li>/</li> <li>455,0</li> <li>2350x1100x1530 mm</li> </ul>



#### **Description**

# Used Sabroe SAB 128 HF MK2 man VI

Used Sabroe SAB 128 HF MK2 compressor unit on NH3. Complete with 1 Sabroe SAB 128 HF MK2 screw compressor, Schorch KA7225M-AB014-151 - 50 Hz - 49,5 kW - 2950 RPM elektromotor, oil separator, Sabroe OWSG 1615 oil cooler, oil filter, pump and a UNISAB S-control panel. The compressor can run as single cooling purpose with another electromotor.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*If requested we are happy to arrange your logistics.



## Your partner for used commercial and industrial refrigeration equipment

































