

Bitzer 2GSL-3K-40S (x4)

Specifications

| Brand | Bitzer |
|--------------------------|--------------------------|
| Туре | 2GSL-3K-40S (x4) |
| Refrigerant | CO2 |
| kW at -20°C/+40°C | 60,0 |
| kW at -30°C/+40°C | 39,5 |
| kW at -40ºC/+40ºC | 24,2 |
| kW at -45ºC/+40ºC | 18,2 |
| Capacity Control | / |
| On steel base frame | / |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Liquid receiver | ✓ |
| Liquid receiver ltr. | 110 |
| Oil separator | ✓ |
| Oil level system AC&R | ✓ |
| Liquid line filter drier | ✓ |
| Control panel | ✓ |
| m3 / h | 20,2 |
| Remarks | Capacities basen on tc = |
| | 0°C |
| Package / Rack | ✓ |
| Sizes | 3400x1300x2300 mm |
| | (LxWxH) |
| Stock | 1 |
| | |



Description

Used Bitzer 2GSL-3K-40S (x4)

Used Bitzer 2GSL-3K-40S (x4) semihermetic reciprocating compressor unit for CO2. Complete with a liquid receiver, liquid separator and a plate heat exchanger. Including active security cooling for standstill times. Two compressors are frequency controlled by two Danfoss ADAP-KOOL Drives. The compressors have a total displacement of 20,2 m³/h. *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics



Your partner for used commercial and industrial refrigeration equipment















Your partner for used commercial and industrial refrigeration equipment











Your partner for used commercial and industrial refrigeration equipment











Your partner for used commercial and industrial refrigeration equipment











