

Bitzer 6G.2Y (x2) & 4N.2Y (x1)

Specifications

Brand	Bitzer
Туре	6G.2Y (x2) & 4N.2Y (x1)
Refrigerant	Freon
kW at -5ºC/+40ºC	206,1
kW at -10ºC/+40ºC	169,9
kW at -20ºC/+40ºC	111,5
kW at -30ºC/+40ºC	68,2
kW at -40ºC/+40ºC	37,0
kW at -45ºC/+40ºC	25,0
Unloaded Start	✓
On steel base frame	1
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	1
Hp/Lp/Op	
Condensing pressure	1
switches	
Oil separator	1
Oil level system AC&R	1
Solenoid Valve	1
m3 / h	373,7
Remarks	SN: 1672714195 - Y.o.b.
	2007
Remarks	SN: 1666105748 - Y.o.b.
	2004
Remarks	SN: 1677105759 - Y.o.b.
	2009





Package / Rack	1	
Sizes	2900x1650x2000 mm (LxWxH)	Description
Stock	1	Used Bitzer 6G.2Y (x2) & 4N.2Y (x1)
		Used Bitzer semi bermetic

Used Bitzer semi-hermetic reciprocating rack on Freon. Complete with a Bitzer 4N.2Y that has a Rotor KF180L25 electric motor - 50 Hz -7,5/11 kW - 980/1470 RPM, Bitzer 6G.2Y (x2) both with a Rotor electric motor - 50 Hz - 30 kW - 1465 RPM, oil separator, oil reservoir, oil level regulator and pressure and safety switches/gauges. The compressor rack has a total displacement of 373,7 m³/h. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment















Your partner for used commercial and industrial refrigeration equipment







	SCHINENBAU GME	Тур 6G.2Y SNr 1666105748 IBH
Fordervolumen m³/h 78,7-153,0	Drehzahl min ⁻¹ 900-1750	
ND/HD max	c. 19 / 25 ba	ar



Your partner for used commercial and industrial refrigeration equipment



	RASCHINENBAU GMBH ade in E.C.	6G.2Y 1677105759
ördervolumen	Drehzahl	120 0
<u>m²/h</u> 78,7-153,0	min -1 900-1750	14
The second second	A CONTRACTOR	
ND/HD n	nax 19 / 25 bar	1. 1. 1. 1. 5 L. 1.

