

Bitzer 4P-15.2Y (x1) & 4T-12.2Y (x2)

Specifications

Brand	Bitzer
Туре	4P-15.2Y (x1) & 4T-12.2Y
	(x2)
Refrigerant	Freon
kW at 0ºC/+40ºC	104,6
kW at -5ºC/+40ºC	86,8
kW at -10ºC/+40ºC	71,3
kW at -20ºC/+40ºC	46,4
kW at -30ºC/+40ºC	28,1
kW at -40ºC/+40ºC	16,4
Unloaded Start	✓
On steel base frame	 Image: A second s
Pressure safety switches	1
Hp/Lp/Op	
Pressure gauges	 Image: A second s
Нр/Lр/Ор	
Liquid receiver	✓
Liquid receiver ltr.	260
Suction accumulator	✓
Oil level system AC&R	 Image: A start of the start of
Liquid line filter drier	 Image: A start of the start of
Solenoid Valve	✓
m3 / h	125,9
Package / Rack	✓
Sizes	2550x1500x2500 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 4P-15.2Y (x1) & 4T-12.2Y (x2)

Used Bitzer 4P-15.2Y (x1) & 4T-12.2Y (x2) semi-hermetic reciprocating compressor rack on Freon. Complete with a Apparatebau Hopfgarten KH 260 NL liquid receiver with a volume of 260 liter, suction accumulator, pressure and safety switches/gauges, oil level system and a liquid line filter drier. The compressors have a total displacement of 125,9 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment















Your partner for used commercial and industrial refrigeration equipment











Your partner for used commercial and industrial refrigeration equipment







