

## Your partner for used commercial and industrial refrigeration equipment

### **Danfoss SH240A4ABE**

### **Specifications**

Brand	Danfoss
Туре	SH240A4ABE
Refrigerant	Freon
kW at $+10^{\circ}$ C/ $+40^{\circ}$ C	72,5
kW at 0ºC/+40ºC	51,5
kW at -5ºC/+40ºC	42,8
kW at -10ºC/+40ºC	35,2
kW at -20ºC/+40ºC	22,9
Sight Glass	1
m3 / h	39,6
Remarks	Y.o.b. 2016
Weight in kg.	107 kg
Sizes	370x370x700 mm
	(LxWxH)
Stock	2



#### Description

#### Used Danfoss SH240A4ABE

Used Danfoss SH240A4ABE scroll compressor on Freon with a sight glass. The compressor has a displacement of 39,6 m<sup>3</sup>/h.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. \*Optionally we can also perform a new paint job and arrange the logistics.



# Your partner for used commercial and industrial refrigeration equipment



Model no: SH240A4ABE	MADE IN FRANCE 380-400/3 - 50H2 460/3 - 60H2 LR 215A MAXOPER.49A Thermally protected system PED. Viside HP side PS 31,1 bar 45 bar TS max 52°C 150°C TS min 35°C 35°C Volume 28,5L 2.5L Lubricant P.O.E. 16052
CC C Source EAL Constraints R410A S Refrigerant: R410A S PROTECTED BY DOMESTIC AND FOREIGN WARNING	A CAUTION
Installation and services that the performed by trained personate (usy) draw the observe three starty warrings could read a survice starty or each of terricing (characteristic of council of the observe terricing) (characteristic of council of terricing) (characteristic of council of terricing) (characteristic of the observe terricing) (characteristic of the observe terricing) (characteristic of the observe terricing) (characteristic of the observed terricing) (characteristic of the observed te	International and the second an



