

Bitzer 4DC-5.2Y-40S

Specifications

| | |
|--------------------------|--|
| Brand | Bitzer |
| Type | 4DC-5.2Y-40S |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 13,3 |
| kW at -5°C/+40°C | 10,7 |
| kW at -10°C/+40°C | 8,5 |
| kW at -20°C/+40°C | 5,0 |
| kW at -30°C/+40°C | 2,6 |
| kW at -40°C/+40°C | 3,0 |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Liquid receiver | ✓ |
| Liquid receiver ltr. | 24,5 |
| Liquid line filter drier | ✓ |
| Sight Glass | ✓ |
| m3 / h | 50 Hz - 26,9 m³/h / 60 Hz - 32,4 m³/h |
| Remarks | Y.o.b. 2007 |
| Condensing Unit | ✓ |
| Sizes | 2050x800x990 mm (LxWxH) |
| Stock | 1 |





Description

Used Bitzer 4DC-5.2Y-40S

Used Bitzer condensing unit on Freon. Complete with 1 Bitzer 4DC-5.2Y-40S semi-hermetic reciprocating compressor, condenser with 3 ebmpapst S4E400-AP02-83 fans - 50/60 Hz - 0,16/0,24 kW - 1430/1700 RPM and an RV-280X498 liquid receiver with a volume of 24,5 liter, liquid line filter drier and pressure safety switches. The compressor has a displacement of 26,9 m³/h at 50 Hz and 32,4 m³/h at 60 Hz. *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.





| | | | | | |
|---|------------|------------------------------------|------------|--|--|
|  | | LEGNAGO VERONA-Italy I-37048 | |  0036 | |
| Type | RV-280X498 | | | | |
| Manufacture- Nr. | 6246604 | | | | |
| Manufacture year | 2006 | | | | |
| Fluids Group | 2 | / | Escludo | / | |
| Category | II | / | Volume V:L | 24.5 | |
| Temperature TS-°C | -10 | 120 | -50 | 120 | |
| Max. permissible press. PS-bar | 33 | 24 | | | |
| Test pressure PT-bar | 47.19 | | | | |



