

Bitzer 6H.2 (x2)

Specifications

Brand	Bitzer
Type	6H.2 (x2)
Refrigerant	Freon
kW at 0°C/+40°C	179,8
kW at -5°C/+40°C	149,8
kW at -10°C/+40°C	123,6
kW at -20°C/+40°C	81,4
kW at -30°C/+40°C	50,2
kW at -40°C/+40°C	27,6
kW at -45°C/+40°C	19,2
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	7,5 l
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m3 / h	137,0 m³/h - 900 RPM & 266,8 m³/h - 1750 RPM
Remarks	Y.o.b. 1996
Package / Rack	✓



Sizes	2950x1520x1600 mm (LxWxH)
-------	------------------------------

Stock	1
-------	---

Description

Used Bitzer 6H.2 (x2)

Used Bitzer 6H.2 (x2) open-type reciprocating compressor rack on Freon. Compressor with Dutchi 200 L4 electromotor - 30 kW - 1475 RPM at 50 Hz. Complete with a AC&R S-9109 liquid receiver with a volume of 7,5 liters, AC&R S-1903 oil separator, oil level system AC&R, pressure and safety switches/gauges and sight glass. The compressors have a total displacement of 137,0 m³/h at 900 RPM & 266,8 m³/h at 1750 RPM.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.









