

## Your partner for used commercial and industrial refrigeration equipment

### Bitzer 2JHC-07K-40S

#### **Specifications**

Brand	Bitzer
Туре	2JHC-07K-40S
Refrigerant	CO2
kW at -30ºC/+40ºC	*6,7
kW at -40ºC/+40ºC	*4,0
Oil level system AC&R	1
m3 / h	50 Hz - 3,48 m³/h / 60 Hz
	- 4,18 m³/h
Remarks	*Capacity based on a
	condensing temperature
	of +0ºC
Weight in kg.	43 kg
Stock	2



#### Description

#### Used Bitzer 2JHC-07K-40S

Used Bitzer 2JHC-07K-40S semihermetic reciprocating compressor for CO2 with an electric oil level system AC&R. The compressor has a displacement of 3,48 m<sup>3</sup>/h at 50 Hz & 4,18 m<sup>3</sup>/h at 60 Hz. \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.



# Your partner for used commercial and industrial refrigeration equipment



BITZER	KÜHLMA			U GMB	Typ 2 S.Nr. 1 H	JHC-0 67871	7K-40S 0200	12t
Nennspannung Mad		e in E.C. Frequ.   Max.Betr.strom		Anlaufstrom		Fördervol.	Drehzahl	
V A 3Ph	VY 3Ph~	Hz	A(Δ)	A (Y)	$A(\Delta)$	A (Y)	m³/h	min <sup>-1</sup>
220-240	380-420	50	6,6	3,8	25,6	14,8	3,48	1450

	KÜHLMA	izer		N. Color	S.Nr. 1	JHC-0 67900	7K-40S 1925	
DIIZER		e in E.C	· ····································					15/15
Nennspann	in the second second	350	Max.Bet	1	Anlaufs	1.0. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	Fördervol.	Drehzahl
and the second second second	VY 3Ph-	Contract of the	$A(\Delta)$ .	A (Y)	$A(\Delta)$	A (Y)	m³/h	min <sup>-1</sup>
1	380-420	50 .	6,6	3,8	25,6	14,8	3,48	1450
265-290	440-480	60	6,6	3,8	25,6	14,8	4,18	1750