

Thermofin TACH.3-091-26-B-L-DE-BD-2

Specifications

Brand	Thermofin
Type	TACH.3-091-26-B-L-DE-BD-2
Product type	Air Cooled Condenser
kW	1047,3
Number of Fans	12
RPM of the Fans	885
Refrigerant	Freon
Air Flow in m ³ /h	246.000
diameter fans Ø	910 mm
Surface (m ²)	3614,9
Tube volume	333 dm ³
Sizes	11830x2300x1450 mm (LxWxH)
Weight	3000 kg
Remarks	Y.o.b. 2011
Stock	1



Description

Used Thermofin TACH.3-091-26-B-L-DE-BD-2

Used Thermofin TACH.3-091-26-B-L-DE-BD-2 air-cooled condenser on NH₃ (Ammonia). Complete EBM-Papst S3G910-CU22-06 - 50/60 Hz - 2,1 kW - 885 RPM - diameter 910 mm and a total airflow of 246.000 m³/h.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning. on demand, we can arrange your shipment.



thermofin GmbH®		CE 0036		thermofin®	
Am Windrad 1				heat exchangers - GERMANY	
D - 08468 Heinsdorfergrund					
Bezeichnung model / modèle		TACH.3-091-26-B-L-DE-BD-2			
Artikel-Nr. article-n° / no. d'article		EP0 000 933			
Projekt-Nr. project-n° / no. de projet		708545 - 010		Geräte-Nr. unit-n° / no. d'appareil 002	
Fertigungsjahr prod. year / année de fabr.		02/2011		Betriebsdruck max working pressure / pression max PS 25 bar	
Rohrvolumen tube volume / volume tubul		333,0 L		Mediumtemp. / medium temp. plage de temp. d'utilis. du fluide TS -30/+120 °C	
Leergewicht empty weight / poids		ca. 3000 kg		Ventilatortemp. / fan temp. plage de temp. d'utilis. des vent -25/+60 °C	
Prüfüberdruck test pressure / pression d'épreuve		PT 28 bar		Prüfmedium test medium / fluide d'épreuve Luft / air	
el. Anschlusswerte / connected load / données électriques					
Ventilator(en) fan(s) / ventilateur(s)		380/480 V		el. Heizung el. defrost - V	
N / Y		25,2 kW		degivrage el. - kW	



