

Mycom 200VLDD-MSX 5.8

Specifications

Brand	Mycom
Type	200VLDD-MSX 5.8
Refrigerant	NH 3 (ammonia)
kW at +10°C/+40°C	1654,4
kW at 0°C/+40°C	1157,0
kW at -5°C/+40°C	954,7
kW at -10°C/+40°C	779,8
kW at -20°C/+40°C	502,0
kW at -30°C/+40°C	303,9
kW at -40°C/+40°C	167,6
kW at -45°C/+40°C	117,7
Electromotor Specs	50/60 Hz - 315 kW - 2965/3575 RPM
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Condensing pressure switches	✓
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓
m3 / h	1850 m ³ /h - 4500 RPM



Remarks	Y.o.b. 2017
Weight in kg.	+ - 4700
Sizes	4200x1600x2540 mm (LxWxH)
Stock	2

Description

Used Mycom 200VLDD-MSX 5.8

Used Mycom 200VLDD-MSX 5.8 screw compressor unit on NH3 (Ammonia) built in 2017. Complete with a WEG 280L-02 electric motor with the following specifications: 50/60 Hz - 315 kW - 2965/3575 RPM, Mayekawa HS7533V-200 oil separator with a volume of 1550 liters, HS-Cooler KS20-AEH-115 L1600 oil cooler, Mycom F50P oil pump, Grundfos TP 40-140/4 A-F-A-BQQE water pump that provides cooling water for the oil cooler, expansion vessel, pressure and safety switches/gauges, Danfoss FC-102N315T4E54H4 frequency regulator and a control cabinet for the compressor with a display.

We can deliver these compressor units with a suitable Evapco LSCE 281 evaporating condenser. Please feel free to contact us for more information!

Unit number 1: running 24000 hours.
Unit number 2: running 21000 hours.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.













