

Sabroe HPO 28

Specifications

Brand	Sabroe
Type	HPO 28
Refrigerant	CO2
Refrigerant type	R744
kW at -20°C/+40°C	611,4*
kW at -30°C/+40°C	418,1*
kW at -40°C/+40°C	271,1*
Electromotor Specs	50 Hz - 132 kW - 1487 RPM
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Oil separator	✓
Sight Glass	✓
Solenoid Valve	✓
Control panel	✓
m3 / h	233
Remarks	Y.o.b. 2012
Remarks	*Capacity based on a condensing temperature of 0°C
Sizes	2500x950x1700 mm (LxWxH)
Stock	2



Description

Used Sabroe HPO 28

Used Sabroe HPO 28 reciprocating compressor on R744 (CO2). Complete with an ABB M2BAT 315 SMB 4 electric motor - 50 Hz - 132 kW - 1487 RPM, Sabroe OVUR 4113D oil separator with a volume of 158 liter and a Unisab 3 controller. The compressor has a displacement of 233 m³/h. *Capacity based on a condensing temperature of 0°C.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.





