

Bitzer 6G.2

Specifications

| | |
|--------------------------|---------------------------|
| Brand | Bitzer |
| Type | 6G.2 |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 106,3 |
| kW at -5°C/+40°C | 88,0 |
| kW at -10°C/+40°C | 72,2 |
| kW at -20°C/+40°C | 46,8 |
| kW at -30°C/+40°C | 28,5 |
| kW at -40°C/+40°C | 15,2 |
| kW at -45°C/+40°C | 10,3 |
| Capacity Control | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Oil level system AC&R | ✓ |
| Sight Glass | ✓ |
| m ³ / h | 78,7 - 153,0 |
| Weight in kg. | 153 |
| Sizes | 630x580x520 mm (LxWxH) |
| Stock | 2 |



Description

Used Bitzer 6G.2

Used Bitzer 6G.2 open-type reciprocating compressor on Freon. Complete with a pressure safety switches, oil level system AC&R S-9110 and sight glass. The compressor has a displacement between 78,7 - 153,0 m³/h at 900 - 1750 RPM.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your shipment.



