

Bitzer 4T-12.2

Specifications

| | |
|--------------------|---------------------------|
| Brand | Bitzer |
| Type | 4T-12.2 |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 32,7 |
| kW at -5°C/+40°C | 27,1 |
| kW at -10°C/+40°C | 22,3 |
| kW at -20°C/+40°C | 14,6 |
| kW at -30°C/+40°C | 8,9 |
| kW at -40°C/+40°C | 4,8 |
| kW at -45°C/+40°C | 3,2 |
| Unloaded Start | ✓ |
| Capacity Control | ✓ |
| Sight Glass | ✓ |
| Solenoid Valve | ✓ |
| m ³ / h | 39,4 |
| Weight in kg. | 146 |
| Sizes | 700x510x470 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4T-12.2

Used Bitzer 4T-12.2 semi-hermetic reciprocating compressor on Freon. Complete with unloaded start, capacity control and a sight glass. The compressor has a displacement of 39,4 m³/h.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.

