

Bitzer 2CC-4.2Y-40S Condensing unit

Specifications

| | |
|--------------------------|--|
| Brand | Bitzer |
| Type | 2CC-4.2Y-40S Condensing unit |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 12,7 |
| kW at -5°C/+40°C | 10,5 |
| kW at -10°C/+40°C | 8,7 |
| kW at -20°C/+40°C | 5,6 |
| kW at -30°C/+40°C | 3,4 |
| kW at -40°C/+40°C | 1,8 |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Liquid receiver | ✓ |
| Liquid receiver ltr. | 13 |
| Oil separator | ✓ |
| Liquid line filter drier | ✓ |
| Sight Glass | ✓ |
| m ³ / h | 16,2 m ³ /h at 50 Hz & 19,6 m ³ /h at 60 Hz |
| Remarks | Y.o.b. 2005 |
| Condensing Unit | ✓ |
| Sizes | 1350x720x850 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 2CC-4.2Y-40S Condensing unit

Used Bitzer 2CC-4.2Y-40S condensing unit on Freon. Complete with a Bitzer 2CC-4.2Y-40S semi-hermetic reciprocating compressor, condenser with 1 Ziehl-Abegg FB045-4EK.4I.6P fan - 50/60 Hz - 0,48/0,73 kW - 1340/1530 RPM - diameter 450 mm, Bitzer FS126 liquid receiver with a volume of 13 liter, oil separator, liquid line filter drier, pressure and safety switches and a control cabinet. The compressor has a displacement of 16,2 m³/h at 50 Hz & 19,6 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new



paint job and arrange the logistics.





