

Mycom 200VLD-L

Specifications

Brand	Mycom
Type	200VLD-L
Refrigerant	NH 3 (ammonia)
kW at 0°C/+40°C	1166,6
kW at -5°C/+40°C	958,5
kW at -10°C/+40°C	778,6
kW at -20°C/+40°C	492,8
kW at -30°C/+40°C	288,8
Electromotor Specs	50/60 Hz - 315 kW - 2970/3565 RPM
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Oil separator	✓
Sight Glass	✓
Control panel	✓
Remarks	Y.o.b. 2010
Weight in kg.	4750
Stock	1



Description

Used Mycom 200VLD-L

Used Mycom / Mayekawa 200VLD-L screw compressor on NH3 (Ammonia). Complete with 2EC IE3-0DP-315LX-2 electric motor - 50/60 Hz - 315 kW - 2970/3565 RPM, Mayekawa HS7533-200-CE oil separator with a volume of 1560 liter, Mayekawa OC15245V oil cooler, Mycom F50P oil pump, 2 Mycom OFC 50 oil filters and a control cabinet with a Mayekawa Mypro-CP3 controller.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.









