

# Bitzer 6GE-34Y-40P (x2)

## Specifications

|                          |                             |
|--------------------------|-----------------------------|
| Brand                    | Bitzer                      |
| Type                     | 6GE-34Y-40P (x2)            |
| Refrigerant              | Freon                       |
| kW at 0°C/+40°C          | 210,4                       |
| kW at -5°C/+40°C         | 175,8                       |
| kW at -10°C/+40°C        | 145,8                       |
| kW at -20°C/+40°C        | 97,2                        |
| kW at -30°C/+40°C        | 61,2                        |
| kW at -40°C/+40°C        | 35,4                        |
| kW at -45°C/+40°C        | 25,4                        |
| On steel base frame      | ✓                           |
| Pressure safety switches | ✓                           |
| Hp/Lp/Op                 |                             |
| Pressure gauges          | ✓                           |
| Hp/Lp/Op                 |                             |
| Liquid receiver          | ✓                           |
| Liquid receiver ltr.     | 228                         |
| Oil separator            | ✓                           |
| Oil level system AC&R    | ✓                           |
| Liquid line filter drier | ✓                           |
| Sight Glass              | ✓                           |
| Solenoid Valve           | ✓                           |
| m3 / h                   | 254                         |
| Remarks                  | Y.o.b. 2014                 |
| Package / Rack           | ✓                           |
| Sizes                    | 2250x940x2050 mm<br>(LxWxH) |



Stock

1

## Description

### Used Bitzer 6GE-34Y-40P (x2)

Used Bitzer 6GE-34Y-40P (x2) semi-hermetic reciprocating compressor rack on Freon. Complete with a Bitzer liquid receiver with a volume of 228 liters, Henry Technologies S-5190-CE oil separator, Henry Technologies S-9109-CE oil reservoir, pressure safety switches/gauges and sight glasses. The compressors have a total displacement of 254,0 m<sup>3</sup>/h at 50 Hz & 306,0 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. \*Optionally we can also perform a new paint job and arrange the logistics.







