

Bitzer 6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1)

Specifications

Brand	Bitzer
Type	6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1)
Refrigerant	Freon
Refrigerant type	R404A
kW at -5°C/+40°C	345,5
kW at -10°C/+40°C	284,5
kW at -20°C/+40°C	185,9
kW at -30°C/+40°C	113,0
kW at -40°C/+40°C	60,3
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	228
Oil separator	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m3 / h	518,3
Remarks	Y.o.b. 2008



(LxWxH)

Stack

330x1360x2060 mm

Description

Used Bitzer 6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1)

Used Bitzer 6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1) semi-hermetic reciprocating compressor rack on Freon. Complete with a Bitzer F2202N liquid receiver with a volume of 228 liters, Henry Technologies S-5203-CE oil separator, Henry Technologies S-9109-CE oil reservoir, brazed heat exchanger, pressure and safety switches/gauges and a liquid line filter drier. The compressors have a displacement of 518,3 m³/h at 50 Hz. *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.







