

Bitzer 4H.2 / 4G.2

Specifications

Brand	Bitzer
Type	4H.2 / 4G.2
Refrigerant	Freon
kW at 0°C/+40°C	130,7
kW at -5°C/+40°C	108,6
kW at -10°C/+40°C	89,3
kW at -20°C/+40°C	58,3
kW at -30°C/+40°C	35,5
kW at -40°C/+40°C	19,3
Electromotor Specs	18,5 kW at 1460 RPM
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	/
Hp/Lp/Op	
Liquid receiver	✓
Oil separator	/
Sight Glass	✓
Remarks	Pulley EM: 220 mm /
	Compr: 220 mm
Remarks	R404a - R22 or other
	freon types
Package / Rack	✓
Sizes	2600x800x1880 mm
	(LxWxH)
Stock	1



Description

Used Bitzer 4H.2 / 4G.2

Used Bitzer 4H.2 / 4G.2 freon compressor rack, complete with pressure safety switches, pessure gauges, liquid receiver, oil separator and sight glass. This unit has a cooling capacity of 130,7 kW at 0°C/+40°C.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Your partner for used commercial and industrial refrigeration equipment







