

Bitzer 4H.2

Specifications

Brand	Bitzer
Type	4H.2
Refrigerant	Freon
kW at 0°C/+40°C	54,8
kW at -5°C/+40°C	45,7
kW at -10°C/+40°C	37,7
kW at -20°C/+40°C	24,8
kW at -30°C/+40°C	15,3
kW at -40°C/+40°C	8,4
Electromotor Specs	15 kW at 1460 RPM
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓
Remarks	# // Electromotor: 15 kW at 1460 RPM // Pulley EM: 200 mm / Pulley compr.: 220 mm
Remarks	R404a - R22 or other freon types



	(LxWxH)
Size	1650x1200x2200 mm

Description

Used Bitzer 4H.2

Used Bitzer 4H.2 freon compressor, complete with unloaded start, pressure safety switches, pressure gauges, liquid receiver, liquid line filter drier, sight glass and control panel. This unit has a cooling capacity of 54,8 kW at 0°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.





