

Bitzer 4H.2 / 6G.2 / 6F.2

Specifications

Brand	Bitzer
Type	4H.2 / 6G.2 / 6F.2
Refrigerant	Freon
kW at -10°C/+40°C	190
kW at -20°C/+40°C	124,5
kW at -30°C/+40°C	76,2
kW at -40°C/+40°C	41,5
Electromotor Specs	16 / 30 / 37
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	20
Oil separator	✓
Liquid line filter drier	✓
Control panel	✓
Remarks	# // Electromotor 16 kW at 1445 RPM (4H.2) // 30 kW at 1475 RPM (6H.2) // 37 kW at 1480 RPM (6F.2) // Evaporator Helpman PLV 24-4
Remarks	R404a - R22 or other freon types



Sizes	3900x1700x2500 mm (LxWxH)
-------	------------------------------

Stock	1
-------	---

Description

Used Bitzer 4H.2 / 6G.2 / 6F.2

Used Bitzer 4H.2 / 6G.2 / 6F.2 freon compressor rack, complete with unloaded start, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, control panel and liquid receiver with a volume of 20 liters.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.







